

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

MC-AnchorSolid E820 - Komponente A · Trade name

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture

Epoxy coating Epoxy impregnation

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone number:

msds@mc-bauchemie.de

Tel.: +49 / (0)700 24112112 (MCR)

Tel:: +48612864565

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS09

· Signal word Warning

(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 1)

· Hazard-determining

components of labelling: epoxide derivates

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)] dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl) oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]

dioxirane

Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane

(1;2)

Polyol epoxy hybrid

oxirane, 2-(chloromethyl)-, polymer with α -hydro- ω -

hydroxypoly[oxy(methyl-1,2-ethanediyl)]

· **Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/

spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical

advice/attention.

P337+P313 If eye irritation persists: Get medical advice/

attention.

• Additional information: Contains epoxy constituents. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when

sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Resin mixture with colouring agents.

Mixture consisting of the following components.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

| Dangerous componer | nts: | | |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--|
| CAS: 1675-54-3 EINECS: 216-823-5 | epoxide derivates Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | 30-60% | |
| EC number: 701-263-0 | Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane and 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 | | |
| CAS: 80-48-8 EINECS: 201-283-5 | methyl toluene-4-sulphonate Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | | |
| CAS: 933999-84-9 | Reaction products of hexane-1,6-diol with 2-(chloromethyl) oxirane (1;2) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | | |
| CAS: 13463-67-7 EINECS: 236-675-5 | titanium dioxide Carc. 2, H351 | | |
| CAS: 2530-83-8 EINECS: 219-784-2 | [3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318 | ≥1-<2.5 | |
| | Polyol epoxy hybrid Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH205 | ≥0.1-<1 | |
| CAS: 9072-62-2 | oxirane, 2-(chloromethyl)-, polymer with α-hydro-ω-hydroxypoly[oxy(methyl-1,2-ethanediyl)] Eye Irrit. 2, H319; Skin Sens. 1B, H317; STOT SE 3, H335; Aquatic Chronic 3, H412 | <i>≥</i> 0.1-<0.8 | |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation Supply fresh air.

After skin contact Instantly wash with water and soap and rinse thoroughly.
 After eye contact Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Rinse out mouth and then drink plenty of water.

Seek medical treatment.

· 4.2 Most important symptoms and effects, both acute and

delayed Allergic reactions

(Contd. on page 4)



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with

water jet or alcohol-resistant foam.

· For safety reasons unsuitable

extinguishing agents

Water with a full water jet.

5.2 Special hazards arising from the substance or

mixture

No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment:

Wear self-contained breathing apparatus.

• Additional information Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and

emergency procedures
6.2 Environmental

Wear protective equipment. Keep unprotected persons away.

precautions:

Inform respective authorities in case product reaches water or

sewage system.

Prevent material from reaching sewage system, holes and cellars.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers: Store only in the original container.

(Contd. on page 5)



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 4)

· Information about storage in

one common storage facility: Store away from foodstuffs.

· Further information about

storage conditions: Keep container tightly sealed.

Storage class 10

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical

values that require

monitoring at the workplace: The product does not contain any relevant quantities of materials

with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls · Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Hand protection Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

• Material of gloves

The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material The exact break trough time has to be found out by the

manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: White

· **Smell:** Characteristic

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 5)

· Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range >200 °C
• Flash point: >100 °C
• Auto-ignition temperature: 184 °C

· pH Not determined.

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.110000 mPas

·Solubility

Water: Not miscible or difficult to mix

· Steam pressure at 20 °C: 0.1 hPa

Density and/or relative density

Density at 20 °C 1.5 g/cm³

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

Self-inflammability: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids
Self-reactive substances and mixtures

Void

Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

Void

· Substances and mixtures, which emit

flammable gases in contact with water

Void Void Void Void

Organic peroxides VoidCorrosive to metals Void

· Oxidising liquids

· Oxidising solids

(Contd. on page 7)



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 6)

· Desensitised explosives Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

10.4 Conditions to avoid
 10.5 Incompatible materials:
 No further relevant information available.

· 10.6 Hazardous

decomposition products: Possible in traces.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

| 1675-54-3 | epoxide (| derivates |
|------------|------------|------------------------------------|
| Dermal | LD50 | 23000 mg/kg (rabbit) |
| 80-48-8 m | ethyl tolu | ene-4-sulphonate |
| Oral | LD50 | 341 mg/kg (rat) |
| 13463-67- | 7 titanium | dioxide |
| Oral | LD50 | >10000 mg/kg (rat) |
| Dermal | LD50 | >10000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >6.8 mg/l (rat) |
| 2530-83-8 | [3-(2,3-ep | oxypropoxy)propyl]trimethoxysilane |
| Oral | LD50 | 8030 mg/kg (rat) |
| Dermal | LD50 | 4248 mg/kg (rabbit) |
| Polyol ep | oxy hybrid | d |
| Oral | LD50 | >2000 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rabbit) |

Skin corrosion/irritation
 Serious eye damage/irritation
 Causes skin irritation.
 Causes serious eye irritation.

Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

(Contd. on page 8)



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 7)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic to | xicity: | |
|-----------------------------|----------------------------------------------|--|
| 1675-54-3 epoxide derivates | | |
| IC50 | >42.6 mg/l (Bak) | |
| LC50/96h | 2 mg/l (Oncorhynchus mykiss) | |
| EC50/48h | 1.8 mg/l (Daphnia magna) | |
| ErC50/72h | 11 mg/l (Selenastrum capricornutum) | |
| 2530-83-8 | [3-(2,3-epoxypropoxy)propyl]trimethoxysilane | |
| LC50/96h | 55 mg/l (Cyp) | |
| EC50/48h | 473 mg/l (Daphnia magna) | |
| ErC50/72h | 255 mg/l (Scenedesmus subspicatus) | |
| Polyol epo | xy hybrid | |
| LC50/96h | 67 mg/l (Leucidus idus) | |
| EC50/48h | 90 mg/l (Daphnia magna) | |

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential
No further relevant information available.

12.4 Mobility in soil
No further relevant information available.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

· 12.6 Endocrine disrupting

propertiesThe product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Remark: Toxic for fish

· Additional ecological information:

• General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

OD.



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023 Version number 21 (replaces version 20) Revision: 22.04.2023

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 8)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

| 14.1 UN number or ID number ADR, IMDG, IATA | UN3082 |
|------------------------------------------------|--------------------------------------------------------------------------|
| 14.2 UN proper shipping name | |
| ADR, IATA | ENVIRONMENTALLY HAZARDOU |
| MDO | SUBSTANCE, LIQUID, N.O.S. (epoxide derivate. ENVIRONMENTALLY HAZARDOU |
| IMDG | SUBSTANCE, LIQUID, N.O.S. (epoxide derivate |
| | MARINE POLLUTANT |
| 14.3 Transport hazard class(es) | |
| ADR | |
| Class | 9 (M6) Miscellaneous dangerous substances a |
| | articles. |
| Label | 9 |
| IMDG, IATA | |
| Class | 9 Miscellaneous dangerous substances a articles. |
| Label | 9 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | III |
| 14.5 Environmental hazards: | |
| Marine pollutant: | Yes |
| | Symbol (fish and tree) |
| Special marking (ADR): | Symbol (fish and tree) |
| Special marking (IATA): | Symbol (fish and tree) |
| 14.6 Special precautions for user | Warning: Miscellaneous dangerous substances a |
| | articles. |
| Kemler Number: | 90 |
| EMS Number: | F-A,S-F |
| Stowage Category | A |

(Contd. on page 10)



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 22.04.2023 Printing date 22.04.2023 Version number 21 (replaces version 20)

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 9)

· Transport/Additional information:

5L · Limited quantities (LQ)

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

· Transport category 3 · Tunnel restriction code (-) · Remarks: 1 kg: LQ

· IMDG Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (EPOXIDE

DERIVATES), 9, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-

tier requirements 200 t

· Qualifying quantity (tonnes) for the application of upper-

tier requirements

500 t

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases Harmful if swallowed. H302

> H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

(Contd. on page 11)



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.04.2023

Version number 21 (replaces version 20)

Trade name MC-AnchorSolid E820 - Komponente A

(Contd. of page 10)

Revision: 22.04.2023

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Department issuing data specification sheet:

Environment protection department.

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous

Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 3

· * Data compared to the previous version altered.

GB