

MAX

TYNTIER[®]
RB401T-E

**ENGINEERED FOR
PERFORMANCE**

TIES UP TO #6 X #6 WITH 19GA. WIRE



**STAND UP TO
MUSCULOSKELETAL
DISEASE**

80 YEAR
ANNIVERSARY

MAX

ENGINEERED FOR PERFORMANCE

TYNTIER[®]

RB401T-E

FEATURES/BENEFITS

1. REDUCES BACK STRAIN

The RB401T-E is an ergonomic solution for backbreaking slab work.

2. ADJUSTABLE HANDLES

Users can adjust the handles to 2 positions, to find the most comfortable fit for their height.

3. TRIGGERLESS TECHNOLOGY

An automatic contact mechanism (Pat. Pending) allows the tool to instantly tie when pushed down over a rebar intersection

4. SHORTER TIE HEIGHT

A Wire Bending Mechanism (Pat. Pending) produces a shorter tie height. Less concrete is needed to fully cover a wire tie.

5. TILT SENSOR

The tilt sensor prevents the tool from tying when angled upward

6. ENCLOSED DESIGN

Greater protection against debris and moisture entering the tool.

7. QUICKLY & EASILY LOAD TIE WIRE

Rapidly load the dual wire coil with the quick load magazine design.

TOOL SPECIFICATIONS

Weight	10.2 lbs
H x W x L	12 3/4" x 16" x 43 3/8"
Tying Speed	Approx. 1/2 Sec./Tie
Rebar Capacity	#3 x #3 to #6 x #6
Wire Series	TW1016T
Wire Diameter	19ga.
Ties Per Coil	Approx. 155-260
Ties Per Charge	Approx. 4600
Coils Per Box	30
Battery	JPL91450A
Voltage	DC 14.4V
Recharge Time	Approx. 80% Capacity-60 minutes 100% Capacity - 80 minutes
Standard Equipment	Battery, Charger, Plastic Carrying Case Short Nose and Long Nose Attachment

APPLICATIONS ▶▶

Commercial Buildings | Foundations | Pavement | Water Treatment Tanks
Road and Bridge Construction | Precast Plants | Basements



2 NOSE ATTACHMENTS AVAILABLE




Requires at least 2" clearance between chaired rebar and the ground.
For smaller clearance, down to 1-1/8", please use the short nose attachment.
This specification varies by rebar combination.

MULTIPLE REBAR COMBINATIONS



4 BARS
MINIMUM #3x#3x#3x#3
MAXIMUM #4x#4x#4x#4



3 BARS
MINIMUM #3x#3x#3
MAXIMUM #7x#4x#4

TW1061T TIE WIRE SERIES



19 ga. Steel Wire



19 ga. Poly Coated Wire



19 ga. Electro Galvanized Wire



19 ga. Buy American Wire

TW1061T-S- STAINLESS STEEL WIRE IS ALSO AVAILABLE AS A SPECIAL ORDER ITEM.

MAX

MAX USA CORP.

205 Express St, Plainview NY 11803

800-223-4293

www.maxusacorp.com

DEALER: